

enatel

CM Series Converter LV >1500W

Low Voltage DC-DC Converter Over 1500W



CM1748 / CM1860

DC CONVERTER
↔

DC OUT
48V / 60V

MAX OUTPUT
1800W

Key Features

- Forced-air cooled by a temperature controlled, high-reliability, monitored fan
- Thermally protected
- Input/output voltage and current protected
- Serial alarm and control interface
- Microprocessor controlled
- Standalone or system operation

Efficient and Reliable

These modular rack mount DC-DC converters allow for easy paralleling of modules to provide redundancy or higher power outputs. Designed for use in modern telecommunication networks and industrial applications, these converters offer unrivalled performance.

The design allows for mounting four modules in a 1U x 19" rack or integrated within our COMPACT systems, Enatel's Energy Manager can be used for system level monitoring and control, or it can operate as a standalone unit. These converters can be configured in combinations to provide multiple voltage outputs, filtering and isolation.

The CM Series 'plug and play' ability allows quick and easy installation and system expansion. These robust, reliable converters are forced-air cooled and automatically return to normal operation following abnormal events.

Modules are New Zealand-made to guarantee design, manufacture and process integrity. Our robust, proven conversion topology utilises only the highest specification components – something rarely offered by others.



CM Series Converter LV >1500W

Specifications



ELECTRICAL		CM1748-48	CM1860-48
DC INPUT RATINGS			
NOMINAL VOLTAGE:	48V		
INPUT VOLTAGE RANGE:	40-60V		43-60V
FUSES	Fuse in the positive input with crowbar diode		
INPUT VOLTAGE PROTECTION:	Auto shutdown, auto restart when voltage restored		
DC OUTPUT RATINGS			
NOMINAL VOLTAGE:	48V		60V
VOLTAGE RANGE:	48-52V		54-65V
MAXIMUM OUTPUT CURRENT:	33.0A (48V DC output min)		30.7A (54V DC output min)
POWER RATING:	1700W		1800W
PEAK EFFICIENCY:	93.50%		92.85%
CURRENT:	Current limit fixed, non-adjustable		Current limit fixed, operates between 54-65V DC
ENVIRONMENTAL REQUIREMENTS			
AMBIENT TEMPERATURE:	-20°C to 70°C [-4°F to 158°F] maximum output power is derated above 50°C [122°F]		
STORAGE TEMPERATURE:	-30°C to 85°C [-22°F to 185°F]		
COMPLIANCES			
SAFETY:	EN 60950-1		
IMMUNITY:	CISPR24		
EMISSIONS:	CISPR22 Class B		
OTHER:	CE & RoHS Compliant		
MECHANICAL			
DIMENSIONS:	WIDTH:	111.5 mm [4.39 in]	
	HEIGHT:	44.0 mm [1.73 in] (1U)	
	DEEP:	282.0 mm [11.1 in] overall (rack depth 260.0 mm [10.24 in])	
WEIGHT:	1.50kg [3.31 lb]		
COOLING:	Forced-air cooled (front to back airflow)		

Due to product development, specifications are subject to change without prior notice.
Pictures may be representative: actual products may differ.

Authorised, valued-added distributor

Australia & New Zealand



Powerbox Australia Pty Ltd

Sydney Head Office
4 Beaumont Road,
Mt Kuring-Gai, NSW 2080
Australia



1800 251 380



sales@powerbox.com.au



powerbox.com.au

Powerbox Pacific Ltd

New Zealand Sales Office
1a Henry Rose Place,
Albany, Auckland
New Zealand 0632



09 4158 320



sales@powerbox.co.nz



powerbox.co.nz